

Section name references in L^AT_EX*

Sebastian Rahtz

2012/07/31

Documentation overview for `hyperref`

The documentation for package `hyperref` consists of several files:

Manual The **USER MANUAL** (also available as HTML).

README The **README** file (also available as text file). Here information is collected that is not yet in the manual: new features, package compatibility, limitations, known problems, ...

ChangeLog This file records the version history (also available as text file).

Options This file provides a short option summary.

Bookmark talk, slides Slides for the talk “PDF information and navigation elements with hyperref, pdfTeX and thumbpdf” at EuroTeX 1999.

Bookmark talk, paper The paper version of the talk.

Source code documentation:

hyperref.dtx This is the source code documentation for hyperref.

backref.dtx “Back referencing from bibliographical citations”

☞ **nameref.dtx** “Section name references in L^AT_EX” (this file)

Contents

1	Introduction	2
2	History	2
3	Implementation	2
3.1	\label stuff	3
3.2	Changes of section macros	5
3.2.1	Class beamer	7
3.2.2	Theorems	8
3.3	Referencing stuff	8
3.4	Usage and frontend	10
3.5	Package ifthen support	11
3.6	Compatibility with varioref	11
3.7	Support for package listings	13

*This file has version number v2.42, last revised 2012/07/31.

1 Introduction

Cross-referencing to include the *name* of the section, rather than just the number or page. This works by redefining some of the inside L^AT_EX macros, so it is vulnerable to future changes.

2 History

Sebastian Rahtz, for Lou Burnard, March 15th 1994;
 SPQR CERN July 1994;
 Last mod. Sept. 3th MG;
 Sept. 19th SPQR;
 April 11th 1995 SPQR (added section formatting hook);
 April 14th 1995 SPQR (compatibility with hyperref);
 June 22 1995 SPQR (removed typeout from Sectionformat);
 September 22 1997 added variorref hacks by Corey Minyard;
 September 28th changes by David Carlisle.
 More recent changes are recorded in ChangeLog.

The versions before 2009/11/27 v2.32 did not expand the title strings (of \section, \caption, ...). Then the behaviour switched to expanding, because this allows to remove unwanted macros (\label, ...). Despite this method is used in package titleref and class memoir, the first feedbacks let me conclude that this is not robust enough. Therefore I wrote package gettitlestring that uses the non-expanding method as default. It also allows me to use this package in package zref-titleref. See the package documentation of package gettitlestring how to change the method. It also provides a hook to remove additional unwanted macros, not supported by the package. Example:

```
\usepackage{gettitlestring}
\GetTitleStringDisableCommands{%
  \let\mylabel\@gobble
  \renewcommand\myindex[2]{}%
}
```

3 Implementation

```
1 <*package>
2 \RequirePackage{refcount}[2006/02/12]
3 \RequirePackage{gettitlestring}[2009/12/18]
4 \RequirePackage{ltxcmds}[2009/12/12]
```

We redefine \label so that it also writes the name of the current section to the .aux file; if the name ends in a dot, we zap it. To allow for the hyperref package, also write fourth and fifth fields (empty by default; used for cross-ref name, and file).

```
\NR@strip@period
5 \def\NR@strip@period#1.\ltx@empty#2\@nil{#1}

\strip@period Macro \strip@period was removed in nameref 2012/07/28 v2.41 and reinserted in
2012/07/31 v2.42 for compatibility reasons with package subfig.
6 \def\strip@period#1.\relax#2\@C@{\#1}
```

```

7 \def\NR@sanitize@labelname{%
8   \@onellevel@sanitize\@currentlabelname
9   \edef\@currentlabelname{%
10     \expandafter\NR@strip@period\@currentlabelname
11     \ltx@empty.\ltx@empty\@nil
12   }%
13 }

```

3.1 \label stuff

Here is tested, whether package `showkeys` is loaded. But if option `final` is used, the macros of `showkeys` are not defined, so we have to check an additional test.

```

\ifNR@showkeys
14 \newif\ifNR@showkeys
15 \NR@showkeysfalse
16 \@ifpackageloaded{showkeys}{%
17   \begingroup
18     \@ifundefined{SK@\@label}{%
19       }{%
20         \global\NR@showkeystrue
21       }%
22   \endgroup
23 }{%
\label@hook
24 \providecommand*{\label@hook}{}%
25 \ltx@GlobalAppendToMacro{\label@hook}{%
26   \NR@sanitize@labelname
27 }

\label
28 \def\label#1{%
29   \@bsphack
30   \begingroup
31   \def\label@name{\#1}%
32   \label@hook
33   \protected@write\@auxout{}{%
34     \string\newlabel{\#1}{%
35       \currentlabel}%
36       \thepage}%
37       \currentlabelname}%
38       \currentHref}%
39   }%
40 }%
41 \endgroup
42 \@esphack
43 }%
44 \ifNR@showkeys
45 \def\label#1{%
46   \@bsphack
47   \SK@\SK@\@label{\#1}%
48   \begingroup
49   \def\label@name{\#1}%
50   \label@hook
51   \protected@write\@auxout{}{%
52     \string\newlabel{\#1}{%

```

```

53      {\@currentlabel}%
54      {\thepage}%
55      {\@currentlabelname}%
56      {\@currentHref}{}%
57      }%
58      }%
59      \endgroup
60      \c@esphack
61      }%
62 \fi

\ltx@label
63 \let\ltx@label\label

```

Needed for the *subeqnarray* package.

```

\slabel
64 \@ifundefined{slabel}{}{%
65   \def\slabel#1{%
66     \c@bsphack
67     \if@filesw
68       \begingroup
69         \def\label@name{\#1}%
70         \label@hook
71         \let\thepage\relax
72         \def\protect{\noexpand\noexpand\noexpand}%
73         \edef\@tempa{%
74           \write\auxout{%
75             \string\newlabel{\#1}{%
76               {\thesubequation}%
77               {\thepage}%
78               {\@currentlabelname}%
79               {\@currentHref}{}%
80             }%
81             }%
82           }%
83         \expandafter\endgroup
84         \@tempa
85         \if@nobreak\ifvmode\nobreak\fi\fi
86       \fi
87       \c@esphack
88     }%
89 }

```

Overload an AMS L^AT_EX command, which uses *\newlabel*. Sigh!

```

\@writetocindents@
90 \def\@writetocindents@{%
91   \begingroup
92   \c@for\@tempa:=-1,0,1,2,3\do{%
93     \immediate\write\auxout{%
94       \string\newlabel{tocindent\@tempa}{%
95         \csname r@tocindent\@tempa\endcsname{}{}{}{}%}
96     }%
97   }%
98 }%
99 \endgroup
100 }

```

3.2 Changes of section macros

Add to the underlying section heading macros so that they note the section name for use by label.

If a section heading or the like has a `\label` in it, we need to extract it, or subsequent processing breaks.

```
\NR@gettitle
101 \def\NR@gettitle#1{%
102   \GetTitleString{#1}%
103   \let\@currentlabelname\GetTitleStringResult
104 }
```

First the numbered sections. While we are about it, put in a useful section formatting macro.

```
\NR@sect
105 \let\NR@sect\@sect
106 \newcounter{section@level}

\@sect
107 \def\@sect#1#2#3#4#5#6[#7]#8{%
108   \setcounter{section@level}{#2}%
109   \NR@gettitle{#7}%
110   \NR@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}]{\Sectionformat{#8}{#2}}%
111 }
```

and now the unnumbered ones

```
\NR@ssect
112 \let\NR@ssect\@sect

\NR@ssect
113 \def\@ssect#1#2#3#4#5{%
114   \NR@gettitle{#5}%
115   \NR@ssect{#1}{#2}{#3}{#4}{\Sectionformat{#5}{#1}}%
116 }
```

Support for class memoir.

```
117 \ltx@ifundefined{ifheadnameref}{%
118   }{%
119   \ltx@ifundefined{M@sect}{%
120     }{%
121     \let\NRorg@M@sect\@sect
122     \def\@sect#1#2#3#4#5#6[#7]#8{%
123       \ifheadnameref
124         \NR@gettitle{#8}%
125       \else
126         \NR@gettitle{#7}%
127       \fi
128       \NRorg@M@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}][{#8}]%
129     }%
130   }%
131 }
```

Parts and chapters are treated differently. sigh. `\@part` and `\@spart` are `\long` because of class memoir.

```

132 \let\NR@part\@part
133 \long\def\@part[#1]{%
134   \NR@gettitle{#1}%
135   \NR@part[{#1}]{#2}%
136 }
137 \let\NR@spart\@spart
138 \long\def\@spart#1{%
139   \NR@gettitle{#1}%
140   \NR@spart{#1}%
141 }
142 \let\NR@chapter\@chapter
143 \def\@chapter[#1]{%
144   \NR@gettitle{#1}%
145   \NR@chapter[{#1}]{#2}%
146 }
147 \ifclassloaded{memoir}{%
148   \ltx@ifUndefined{ifheadnameref}{%
149     }{%
150       \def\@chapter[#1]{%
151         \ltx@ifUndefined{ch@pt@c}{%
152           \NR@gettitle{#1}%
153         }{%
154           \ifx\ch@pt@c\ltx@empty
155             \NR@gettitle{#2}%
156           \else
157             \def\NR@temp{#1}%
158             \ifx\NR@temp\ltx@empty
159               \expandafter\NR@gettitle\expandafter{\ch@pt@c}%
160             \else
161               \ifheadnameref
162                 \NR@gettitle{#1}%
163               \else
164                 \expandafter\NR@gettitle\expandafter{\ch@pt@c}%
165               \fi
166             \fi
167           \fi
168         }%
169       \NR@chapter[{#1}]{#2}%
170     }%
171   }{%
172 }
173 \let\NR@schapter\@schapter
174 \def\@schapter#1{%
175   \NR@gettitle{#1}%
176   \NR@schapter{#1}%
177 }
```

Captions

```

178 \AtBeginDocument{%
179   \ifpackageloded{hyperref}{%
180     \ifpackagelater{hyperref}{2009/12/05}{%
181       \gobble\firstofone
182     }{%
183       \let\NR@@caption\caption
184       \long\def\@caption#1[#2]{%
```

```

185      \NR@getttitle{#2}%
186      \NR@@caption{#1}{#2}%
187  }%
188 }%
189 \@ifpackagelloaded{longtable}{%
190   \let\NRorg@LT@c@option\LT@c@option
191   \def\LT@c@option#1[#2]#3{%
192     \NRorg@LT@c@option{#1}[#2]{#3}%
193     \def\@tempa{#2}%
194     \ifx\@tempa\@empty
195     \else
196       \NR@getttitle{#2}%
197     \fi
198   }%
199 }{%

```

Environment ‘description’.

```

200 \ltx@ifUndefined{descriptionlabel}{%
201 }{%
202   \let\NRorg@descriptionlabel\descriptionlabel
203   \def\descriptionlabel#1{%
204     \NR@getttitle{#1}%
205     \NRorg@descriptionlabel{#1}%
206   }%
207 }%
208 }

```

Compatibility for package titlesec.

```

209 \AtBeginDocument{%
210   \@ifpackagelloaded{titlesec}{%
211     \let\NRorg@ttl@sect@i\ttl@sect@i
212     \def\ttl@sect@i#1#2[#3]{%
213       \NR@getttitle{#4}%
214       \NRorg@ttl@sect@i{#1}{#2}{#3}{#4}%
215     }%
216   }{%
217 }

```

3.2.1 Class beamer

```

218 \@ifclassloaded{beamer}{%
219   \def\NR@PatchBeamer#1{%
220     \expandafter\let\csname NRorg@beamer@#1\expandafter\endcsname
221           \csname beamer@#1\endcsname
222     \begingroup
223     \edef\x{\endgroup
224       \long\def\expandafter\noexpand\csname beamer@#1\endcsname
225         [####1]{% hash-ok
226           \noexpand\NR@getttitle{####1}%
227           \expandafter\noexpand\csname NRorg@beamer@#1\endcsname
228             [####1]]%
229         }%
230       }%
231     \x
232   }%
233   \NR@PatchBeamer{section}%
234   \NR@PatchBeamer{subsection}%
235   \NR@PatchBeamer{subsubsection}%

```

```

236 }{%
237 \ltx@ifundefined{@opargbegintheorem}{}{%
238   \let\NRorg@opargbegintheorem\opargbegintheorem
239   \def\opargbegintheorem#1#2#3{%
240     \NR@gettitle{#3}%
241     \NRorg@opargbegintheorem{#1}{#2}{#3}%
242   }%
243 }
244 \AtBeginDocument{%
245   \ifpackageloaded{amsthm}{%
246     \let\NRorg@begintheorem\begintheorem
247     \begingroup
248       \edef\x{\macro:\string#1\string#2[\string#3]}%
249       \onelevel@sanitize\x
250       \def\y#1->#2\@nil{#1}%
251       \edef\z{\expandafter\y\meaning\@begintheorem->\@nil}%
252       \onelevel@sanitize\z
253     \expandafter\endgroup
254     \ifx\x\z
255       \def\@begintheorem#1#2[#3]{%
256         \NR@gettitle{#3}%
257         \NRorg@begintheorem{#1}{#2}{#3}%
258       }%
259     \fi
260   }{%
261 }

```

3.3 Referencing stuff

We default the label and hypertext reference to be empty.

```

262 \providecommand*{\@currentlabelname}{}%
263 \providecommand*{\@currentHref}{}%

```

Since the second part of the preserved reference now has five parts (number, page, name, hypertext reference and file), we need extra utility macros:

```

\@firstoffive
264 \long\def\@firstoffive#1#2#3#4#5{#1}

\@secondoffive
265 \long\def\@secondoffive#1#2#3#4#5{#2}

\@thirdoffive
266 \long\def\@thirdoffive#1#2#3#4#5{#3}

\@fourthoffive
267 \long\def\@fourthoffive#1#2#3#4#5{#4}

\@offive
268 \long\def\@fifthoffive#1#2#3#4#5{#5}

```

We have to redefine `\ref` and `\pageref` to know about extra reference elements. Make them robust, and compatible with Babel. The Babel switch is mimicked if not already defined. Some support for package `showkeys` is implemented. If option `notref` of that package is set, `\SK@ref` has the meaning of `\empty`.

```

\@safe@activestru $\backslash$ 
269 \providecommand*\@safe@activestru $\backslash$ {}%
\@safe@activesfa $\backslash$ 
270 \providecommand*\@safe@activesfa $\backslash$ {}%
\NR@setref
271 \def\NR@setref#1{%
272   \begingroup
273     \@safe@activestru $\backslash$ 
274     \expandafter
275   \endgroup
276   \expandafter\NR@setref\csname r@#1\endcsname
277 }

\NR@setref
278 \def\NR@setref#1{%
279   \ifx\@undefined#1%
280     \let#1\relax
281   \fi
282   \setref#1%
283 }

\T@ref
284 \def\T@ref#1{%
285   \NR@setref{#1}\@firstoffive{#1}%
286 }%

\T@pageref
287 \def\T@pageref#1{%
288   \NR@setref{#1}\@secondoffive{#1}%
289 }%

290 \ifNR@showkeys
291   \ifx\SK@ref\empty
292   \else

\T@ref
293 \def\T@ref#1{%
294   \@safe@activestru $\backslash$ 
295   \SK@\SK@ref{#1}%
296   \@safe@activesfa $\backslash$ 
297   \NR@setref{#1}\@firstoffive{#1}%
298 }%

\T@pageref
299 \def\T@pageref#1{%
300   \@safe@activestru $\backslash$ 
301   \SK@\SK@ref{#1}%
302   \@safe@activesfa $\backslash$ 
303   \NR@setref{#1}\@secondoffive{#1}%
304 }%

305 \fi
306 \fi

```

Package `hyperref` uses its own definitions of `\ref` and `\pageref` because it extends the syntax by the star form. `\DeclareRobustCommand` is used by `hyperref`. Package `nameref` can be loaded before, after `hyperref` or after `hyperref`'s definitions in `\AtBeginDocument`.

```
307 \@ifpackageloaded{hyperref}{%
308 }{%
```

```
\ref
309 \DeclareRobustCommand{\ref}{\T@ref}%
\nameref
310 \DeclareRobustCommand{\nameref}{\T@nameref}%
311 }
```

3.4 Usage and frontend

Access the (third) name part with `\nameref`:

```
\T@nameref
312 \def\T@nameref#1{%
313   \begingroup
314   \let\label\@gobble
315   \NR@setref{\#1}\@thirdoffive{\#1}%
316   \endgroup
317 }%
318 \ifNR@showkeys
319   \ifx\SK@ref\empty
320   \else
321     \def\T@nameref#1{%
322       \csname\active@true\endcsname
323       \SK@\SK@{\ref{\#1}}%
324       \csname\active@false\endcsname
325     \begingroup
326     \let\label\@gobble
327     \NR@setref{\#1}\@thirdoffive{\#1}%
328     \endgroup
329   }%
330 \fi
331 \fi

332 %\@ifclassloaded{memoir}{%
333 %  \ltx@IfUndefined{@mem@titlerefno link}\ltx@secondoftwo{%
334 %    \ltx@IfUndefined{@mem@titleref}\ltx@secondoftwo\ltx@firstoftwo
335 %  }%
336 %}\ltx@secondoftwo
337 %}%
338 % \DeclareRobustCommand*\nameref{%
339 %   \@ifstar\mem@titlerefno link\mem@titleref
340 % }%
341 %}{%
```



```
\nameref
342 \DeclareRobustCommand*\nameref{%
343   \@ifstar\T@nameref\T@nameref
344 }%
345 }%
```

```

\Nameref An extended form which gives title and page number.
346 \def\Nameref#1{'\nameref{\#1}' on page-\pageref{\#1} }

\Sectionformat The default for \Sectionformat
347 \providecommand\Sectionformat[2]{\#1}

```

3.5 Package ifthen support

Package ifthen's `\isodd` does not work with `\pageref` because of the extra link and the star form. Therefore we need an expandable variant.

Unfortunately there is no hook in `\ifthenelse` in order to provide expandable versions without link of `\ref` and `\pageref`. As possible target I could only find `\begingroup`:

```

348 \@ifpackageloaded{ifthen}{%
349   \let\NROrg@ifthenelse\ifthenelse
350   \def\ifthenelse{%
351     \let\begingroup\NR@TE@begingroup
352     \NROrg@ifthenelse
353   }%
354   \let\NROrg@begingroup\begingroup
355   \def\NR@TE@begingroup{%
356     \let\begingroup\NROrg@begingroup
357     \begingroup
358     \def\ref##1{\getrefbykeydefault{\##1}{}{??}}%
359     \def\pageref##1{\getrefbykeydefault{\##1}{page}{0}}%
360   }%
361 }{%

```

3.6 Compatibility with variorref

[This section was derived by Corey Minyard `minyard@acm.org` from the `variorref` package]

```

362 \AtBeginDocument{%
363   \ifx\csname @@vpageref\endcsname\relax
364   \else
365     \def\@@vpageref#1[#2]#3{%
366       \begingroup
367         \csname @safe@activestrue\endcsname
368         \edef\x{#3}%
369         \onelevel@sanitize\x
370         \toks@{%
371           \NR@vpageref{\#1}[{\#2}]%
372         }%
373         \edef\x{\endgroup
374           \the\toks@\{x\}%
375         }%
376         \x
377       }%
378     \def\NR@vpageref#1[#2]#3{%
379       \leavevmode\unskip
380       \global\advance\c@vrcnt\@ne
381       \@ifundefined{r@\the\c@vrcnt@vr}%
382         {\@namedef{r@\the\c@vrcnt@vr}{{?}{?}{?}{?}{?}}{}}{}}{%
383       \edef\@tempa{%
384         \expandafter\expandafter\expandafter
385         \secondoffive\csname r@\the\c@vrcnt@vr\endcsname

```

```

386      }%
387      \@ifundefined{r@\the\c@vrcnt @xvr}%
388      { \@namedef{r@\the\c@vrcnt @xvr}{\{\?\?\}\{\?\?\}\{\}\{\}\{\}}\{\}%
389      \edef\@tempb{%
390          \expandafter\expandafter\expandafter
391          \@secondoffive\csname r@\the\c@vrcnt @xvr\endcsname
392      }%
393      \{%
394          \let\@currentlabel\empty
395          \expandafter\label\expandafter{\the\c@vrcnt @xvr}%
396      }%
397      \ifx\@tempa\@tempb
398      \else
399          \vref@err{%
400              \noexpand\vref at page boundary %
401              \@tempb-\@tempa\space (may loop)%
402          }%
403      \fi
404      \@ifundefined{r@##3}{\@namedef{r@##3}{\{\?\?\}\{\?\?\}\{\}\{\}\{\}}\{\}%
405      \edef\thevpagerefnum{%
406          \expandafter\expandafter\expandafter
407          \@secondoffive\csname r@##3\endcsname
408      }%
409      \ifx\thevpagerefnum\@undefined
410          \space
411      \else
412          \vref@space
413      \fi
414      \ifx\@tempa\thevpagerefnum
415          #1%
416      \else
417          #2%
418          \is@pos@number\thevpagerefnum{%
419              \is@pos@number\@tempa{%
420                  \@tempcnta\@tempa
421                  \advance\@tempcnta\@ne
422              }{%
423                  \@tempcnta\maxdimen
424              }%
425              \ifnum \thevpagerefnum =\@tempcnta
426                  \ifodd\@tempcnta
427                      \if@twoside
428                          \reftextfaceafter
429                      \else
430                          \reftextafter
431                      \fi
432                  \else
433                      \reftextafter
434                  \fi
435              \else
436                  \advance\@tempcnta-2 %
437                  \ifnum \thevpagerefnum =\@tempcnta
438                      \ifodd\@tempcnta
439                          \reftextbefore
440                      \else
441                          \if@twoside
442                              \reftextfacebefore

```

```

443      \else
444          \ref{textbefore}
445      \fi
446      \fi
447      \else
448          \ref{textfaraway}{#3}%
449      \fi
450      \fi
451  }{%
452      \ref{textfaraway}{#3}%
453  }%
454  \fi
455 {%
456      \let\@currentlabel\@empty
457      \expandafter\label\expandafter{\the\c@vrcnt \vr}%
458  }%
459 }%
460 \DeclareRobustCommand\vnameref[1]{%
461     \unskip~\nameref{#1}%
462     \vphantom{\unskip}\vphantom{#1}%
463 }%
464 \fi
465 }

466 \@ifundefined{@Refstar}{%
467 \def\T{@Ref#1}{%
468     \NR@setref{#1}\NR@MakeUppercaseFirstOfFive{#1}%
469 }%
470 \def\NR@MakeUppercaseFirstOfFive#1#2#3#4#5{%
471     \MakeUppercase#1%
472 }%
473 }{%
474 \AtBeginDocument{%
475 \ifpackageloaded{variorref}{%
476     \ifundefined{@Refstar}{%
477         \DeclareRobustCommand*\Ref[1]{%
478             \T@Ref{#1}%
479         }%
480     }{%
481 }{%
482 }%

```

3.7 Support for package `listings`

```

483 \AtBeginDocument{%
484 \ifpackageloaded{listings}{%
485     \let\NROrg@lst@MakeCaption\lst@MakeCaption
486     \def\lst@MakeCaption{%
487         \ifx\lst@label\@empty
488         \else
489             \let\@currentlabelname\lst@caption
490         \fi
491         \NROrg@lst@MakeCaption
492     }%
493 }{%
494 }
495 
```

4 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\@C@C	6	\@safe@activestru e
\@C@vpageref	365 <u>269</u> , <u>273</u> , <u>294</u> , <u>300</u> , <u>322</u>
\@auxout	<u>33</u> , <u>51</u> , <u>74</u> , <u>93</u>	\@schapter <u>173</u> , <u>174</u>
\@begintheorem	\@secondoffive
	<u>246</u> , <u>251</u> , <u>255</u> <u>265</u> , <u>288</u> , <u>303</u> , <u>385</u> , <u>391</u> , <u>407</u>
\@bsphack	29, <u>46</u> , <u>66</u>	\@sect <u>105</u> , <u>107</u>
\@caption <u>183</u> , <u>184</u>	\@setref <u>282</u>
\@chapter	<u>142</u> , <u>143</u> , <u>150</u>	\@spart <u>137</u> , <u>138</u>
\@currentHref <u>38</u> , <u>56</u> , <u>79</u> , <u>263</u>	\@ssect <u>112</u> , <u>113</u>
\@currentlabel	\@tempa <u>73</u> , <u>84</u> , <u>92</u> , <u>94</u> , <u>95</u> , <u>193</u> , <u>194</u> , <u>383</u> , <u>397</u> , <u>401</u> , <u>414</u> , <u>419</u> , <u>420</u>
\@currentlabelname <u>8</u> , <u>9</u> , <u>10</u> , <u>37</u> , <u>55</u> , <u>78</u> , <u>103</u> , <u>262</u> , <u>489</u>	\@tempb <u>389</u> , <u>397</u> , <u>401</u>
\@empty <u>194</u> , <u>291</u> , <u>319</u> , <u>394</u> , <u>456</u> , <u>487</u>	\@tempcnta <u>420</u> , <u>421</u> , <u>423</u> , <u>425</u> , <u>426</u> , <u>436</u> , <u>437</u> , <u>438</u>
\@esphack	42, <u>60</u> , <u>87</u>	\@thirdoffive <u>266</u> , <u>315</u> , <u>327</u>
\@fifthoffive <u>268</u>	\@undefined <u>279</u> , <u>409</u>
\@firstoffive	<u>264</u> , <u>285</u> , <u>297</u>	\@vpageref <u>462</u>
\@firstofone <u>180</u> , <u>181</u>	\@writetocindents@ <u>90</u>
\@for <u>92</u>	
\@fourthoffive <u>267</u>	A
\@gobble <u>180</u> , <u>314</u> , <u>326</u>	\advance <u>380</u> , <u>421</u> , <u>436</u>
\@ifclassloaded	\AtBeginDocument
	<u>147</u> , <u>218</u> , <u>332</u> <u>178</u> , <u>209</u> , <u>244</u> , <u>362</u> , <u>474</u> , <u>483</u>
\@ifpackagelater <u>180</u>	
\@ifpackageloading	B
	<u>16</u> , <u>179</u> , <u>189</u> , <u>210</u> , <u>245</u> , <u>307</u> , <u>348</u> , <u>475</u> , <u>484</u>	\begingroup <u>17</u> , <u>30</u> , <u>48</u> , <u>68</u> , <u>91</u> , <u>222</u> , <u>247</u> , <u>272</u> , <u>313</u> , <u>325</u> , <u>351</u> , <u>354</u> , <u>356</u> , <u>357</u> , <u>366</u>
\@ifstar <u>339</u> , <u>343</u>	
\@ifundefined	C
	<u>18</u> , <u>64</u> , <u>381</u> , <u>387</u> , <u>404</u> , <u>466</u> , <u>476</u>	\c@vrcnt <u>380</u> , <u>381</u> , <u>382</u> , <u>385</u> , <u>387</u> , <u>388</u> , <u>391</u> , <u>395</u> , <u>457</u>
\@mem@titleref <u>339</u>	\ch@pt@c <u>154</u> , <u>159</u> , <u>164</u>
\@mem@titlerefno link <u>339</u>	\csname <u>95</u> , <u>220</u> , <u>221</u> , <u>224</u> , <u>227</u> , <u>276</u> , <u>363</u> , <u>367</u> , <u>385</u> , <u>391</u> , <u>407</u>
\@namedef	<u>382</u> , <u>388</u> , <u>404</u>	
\@ne <u>380</u> , <u>421</u>	
\@nil	<u>5</u> , <u>11</u> , <u>250</u> , <u>251</u>	D
\@offive <u>268</u>	\DeclareRobustCom-
\@onelevel@sanitize <u>8</u> , <u>249</u> , <u>252</u> , <u>369</u>	mand <u>309</u> , <u>310</u> , <u>338</u> , <u>342</u> , <u>460</u> , <u>477</u>
\@opargbegintheorem <u>238</u> , <u>239</u>	
\@part <u>132</u> , <u>133</u>	F
\@safe@activesfalse <u>270</u> , <u>296</u> , <u>302</u> , <u>324</u>	\fi <u>62</u> , <u>85</u> , <u>86</u> , <u>127</u> , <u>165</u> , <u>166</u> , <u>167</u> , <u>197</u> , <u>259</u> , <u>281</u> , <u>305</u> , <u>306</u> , <u>330</u> , <u>331</u> , <u>403</u> , <u>413</u> , <u>431</u> , <u>434</u> ,

<p style="text-align: center;">G</p> <p>\getrefbykeydefault 358, 359 \GetTitleString 102 \GetTitleStringResult 103 \global 20, 380</p>	<p style="text-align: center;">M</p> <p>\ltx@label 63 \ltx@secondoftwo 333, 334, 336 \ltx@sect 121, 122 \MakeUppercase 471 \maxdimen 423 \meaning 251</p>	
<p style="text-align: center;">I</p> <p>\if@filesw 67 \if@nobreak 85 \if@twoside 427, 441 \ifheadnameref 123, 161 \ifNR@showkeys 14, 44, 290, 318 \ifnum 425, 437 \ifodd 426, 438 \ifthenelse 349, 350 \ifvmode 85 \ifx 154, 158, 194, 254, 279, 291, 319, 363, 397, 409, 414, 487 \immediate 93 \is@pos@number 418, 419</p>	<p style="text-align: center;">N</p> <p>\Nameref 346 \nameref 338, 342, 346, 461 \newcounter 106 \newif 14 \newlabel 34, 52, 75, 94 \nobreak 85 \noexpand 72, 224, 226, 227, 400 \NR@@caption 183, 186 \NR@@setref 276, 278 \NR@@vpageref 371, 378 \NR@chapter 142, 145, 169 \NR@gettitle 101, 109, 114, 124, 126, 134, 139, 144, 152, 155, 159, 162, 164, 175, 185, 196, 204, 213, 226, 240, 256</p>	<p style="text-align: center;">P</p> <p>\pageref 310, 346, 359 \protect 72 \protected@write 33, 51 \providecommand 24, 262, 263, 269, 270, 347</p>
<p style="text-align: center;">L</p> <p>\label 28, 63, 314, 326, 395, 457 \label@hook 24, 32, 50, 70 \label@name 31, 49, 69 \leavevmode 379 \let 63, 71, 103, 105, 112, 121, 132, 137, 142, 173, 183, 190, 202, 211, 220, 238, 246, 280, 314, 326, 349, 351, 354, 356, 394, 456, 485, 489 \long 133, 138, 184, 224, 264, 265, 266, 267, 268 \lst@@caption 489 \lst@label 487 \lst@MakeCaption 485, 486 \LT@cc@ption 190, 191 \ltx@empty 5, 11, 154, 158 \ltx@firstoftwo 334 \ltx@GlobalAppend- ToMacro 25 \ltx@IfUndefined 117, 119, 148, 151, 200, 237, 333, 334</p>	<p style="text-align: center;">R</p> <p>\Ref 477 \ref 309, 358 \reftextafter 430, 433 \reftextbefore 439, 444 \reftextfaceafter 428 \reftextfacebefore 442 \reftextfaraway 448, 452 \relax 6, 71, 280, 363 \RequirePackage 2, 3, 4</p>	<p style="text-align: center;">S</p> <p>\Sectionformat 110, 115, 347 \setcounter 108 \SK@ 47, 295, 301, 323 \SK@@label 47 \SK@@ref 295, 301, 323 \SK@ref 291, 319 \slabel 64 \space 401, 410 \string 34, 52, 75, 94, 248 \strip@period 6</p>
		<p style="text-align: center;">T</p> <p>\T@nameref 312, 343 \T@pageref 287, 299, 310 \T@Ref 467, 478 \T@ref 284, 293, 309 \the 374, 381, 382, 385, 387, 388, 391, 395, 457 \thepage 36, 54, 71, 77 \thesubequation 76 \thepagerefnum 405, 414, 418, 425, 437 \toks@ 370, 374</p>

\ttl@sect@i . . . 211, 212 \vref@err 399 249, 254, 368,
 \unskip . . . 379, 461, 462 \vref@space 409, 412 369, 373, 374, 376
 U
 V
 \vnameref 460 \write 74, 93 \y 250, 251
 \ref 400 \x 223, 231, 248, **X** **Y**
 Z
 \z 251, 252, 254