

The C++ Programming Language

An Example of C++ to C Translation

Outline

Introduction
C++ Source Code
C Source Code

1

Introduction

- The following slides illustrate the result of compiling C++ code into C code using the AT&T cfront translator.
- The example illustrates the use of data abstraction, single inheritance, and dynamic binding.
- Note that the C source code is over twice as long as the C++ source code...

2

C++ Source Code

• C++ Source Code

```
extern "C" { extern int printf (char *, ...); }

enum {
    ZERO, ONE, TEN = 10,
    HUNDRED = 100, THOUSAND = 1000
};

class Base {
private:
    int B_private_Data;
protected:
    int B_protected_Data;
public:
    int B_public_Data;

    Base (int arg = ONE) : B_private_Data (arg + THOUSAND),
                           B_protected_Data (arg + HUNDRED),
                           B_public_Data (arg) {}

    ~Base (void) {}

    int B_getPrivate_Data (void) { return B_private_Data; }

    virtual int F1 (void) = 0;
    virtual int F2 (void) { return B_private_Data; }
};
```

3

C++ Source Code (cont'd)

• e.g.,

```
class Derived : public Base {
private:
    int D_private_Data;
public:
    int D_public_Data;
    Derived (int arg = ZERO) : D_private_Data (arg),
                               D_public_Data (arg),
                               Base (arg) {}
    ~Derived (void) {}

    int D_getPrivate_Data (void) { return D_private_Data; }

    virtual int F1 (void) {
        return B_protected_Data;
    }

    virtual int F2 (void) {
        return B_protected_Data + TEN + ONE;
    }
/*
    Derived inherits:
    B_get_private_data, B_public_data, B_protected_data
*/
};
```

4

C++ Source Code (cont'd)

- e.g.,

```
int main (void) {
    Base     *bp = new Derived; // defaults to 0
    Derived d (2);

    printf ("%d\n", d.D_public_Data ); // 2
    d.D_public_Data = TEN;
    printf ("%d\n", d.D_public_Data); // 10

    printf ("%d\n", bp->B_getPrivate_Data () ); // 1000
    printf ("%d\n", d.D_getPrivate_Data () ); // 2

    /* Elide virtual function call! */
    printf ("%d\n", d.F1 () ); // 102

    /* Virtual function call! */
    printf ("%d\n", bp->F2 () ); // 111
    delete bp;
    /* Derived d destructor implicitly called. */
    return 0;
}
```

5

C Source Code

- Cfront output

```
/* Dynamic memory functions */
extern void *_vec_new (void *, int, int, void *);
extern void _vec_delete (void *, int, int, void *, int, int);
extern void *_nw_FUi (unsigned int);
extern void _dl_FPv (void *);

extern int printf (char *,...);

/* Type decls for multiple and single inheritance. */
typedef int (*_vptp) ();

struct _mptr {
    short d; short i; _vptp f;
};

extern struct _mptr *_ptbl_vec_c_src_C [];

enum _E1 {
    ZERO = 0, ONE = 1, TEN = 10,
    HUNDRED = 100, THOUSAND = 1000
};
```

6

C Source Code (cont'd)

- e.g.,

```
struct Base { /* sizeof Base == 16 */
    int B_private_Data__4Base;
    int B_protected_Data__4Base;
    int B_public_Data__4Base;
    struct _mptr *_vptr__4Base; /* Compiler generated. */
};

/* Base class constructor */
static struct Base *
__ct__4BaseFi (struct Base *__0this, int __0arg) {
    /* The following 5 lines are the compiler-generated preamble. */
    if (__0this || !__0this)
        __0this =
            ((struct Base *) __nw_FUi (sizeof (struct Base)))
            (((__0this->_vptr__4Base =
                (struct _mptr *) __ptbl_vec_c_src_C_[0]),
            /* User constructor code starts here! */
            (__0this->B_private_Data__4Base =
                (__0arg + 1000)),
            (__0this->B_protected_Data__4Base =
                (__0arg + 100)),
            (__0this->B_public_Data__4Base =
                __0arg));
    ;
    return __0this;
}
```

7

C Source Code (cont'd)

- e.g.,

```
/* Base class destructor */
static char
__dt__4BaseFv (struct Base *__0this, int __0__free) {
    if (!__0this)
        __0this->_vptr__4Base =
            (struct _mptr *) __ptbl_vec_c_src_C_[0];
    /* User destructor code would go here. */
    if (__0this)
        if (__0__free & 1)
            _dl_FPv ((char *) __0this);
}

static int
B_getPrivate_Data__4BaseFv (struct Base *__0this) {
    return __0this->B_private_Data__4Base;
}

static int
F2__4BaseFv (struct Base *__0this) {
    return __0this->B_private_Data__4Base;
}
```

8

C Source Code (cont'd)

- e.g.,

```

struct Derived { /* sizeof Derived == 24 */
    int B_private_Data__4Base;
    int B_protected_Data__4Base;
    int B_public_Data__4Base;
    struct __mptr *__vptr__4Base;
    int D_private_Data__7Derived;
    int D_public_Data__7Derived;
};

/* Derived class constructor */
static struct Derived *
__ct__7DerivedFi (struct Derived *__0this, int __0arg) {
    /* The following 7 lines are the compiler-generated preamble. */
    if (__0this ||
        (__0this = (struct Derived *))
        __nw_FUi (sizeof (struct Derived)))
        (((__0this = (struct Derived *)
            __ct__4BaseFi (((struct Base *) __0this), __0arg)),
        __0this->__vptr__4Base =
            (struct __mptr *)__ptbl_vec_c_src_C_[1]),
        /* User constructor code goes here. */
        (__0this->D_private_Data__7Derived = __0arg),
        (__0this->D_public_Data__7Derived = __0arg))
    ;
    return __0this;
}

```

9

C Source Code (cont'd)

- e.g.,

```

/* Derived class destructor */
static char
__dt__7DerivedFv (struct Derived *__0this, int __0_free) {
    if (__0this) {
        __0this->__vptr__4Base =
            (struct __mptr *)__ptbl_vec_c_src_C_[1];
        /* User destructor code goes here. */
        if (__0this) {
            __dt__4BaseFv (((struct Base *) __0this), (int) 0);
            if (__0_free & 1)
                __dl_FPV ((char *) __0this);
        }
    }
}

static int
D_getPrivate_Data__7DerivedFv (struct Derived *__0this) {
    return __0this->D_private_Data__7Derived;
}

static int
F1__7DerivedFv (struct Derived *__0this) {
    return __0this->B_protected_Data__4Base;
}

static int
F2__7DerivedFv (struct Derived *__0this) {
    return ((__0this->B_protected_Data__4Base + 10) + 1);
}

```

10

C Source Code (cont'd)

- e.g.,

```

int main (void) {
    _main ();
{
    struct Base *__1bp; struct Derived __1d;

    __1bp = (struct Base *)
        __ct__7DerivedFi ((struct Derived *) 0, (int) 0);
    __ct__7DerivedFi (&__1d, 2);

    printf ((char *) "%d\n", __1d.D_public_Data__7Derived);

    __1d.D_public_Data__7Derived = 10;
    printf ("%d\n", __1d.D_public_Data__7Derived);

    printf ("%d\n", B_getPrivate_Data__4BaseFv (__1bp));
    printf ("%d\n", D_getPrivate_Data__7DerivedFv (&__1d));
    printf ("%d\n", F1__7DerivedFv (&__1d));

    /* Virtual function call */
    printf ((char *) "%d\n",
        (((((int (*) ()) (__1bp->__vptr__4Base[2]).f)))+
        (((struct Base *) (((char *) __1bp))
        + (__1bp->__vptr__4Base[2]).d))));

    __dt__4BaseFv (__1bp, 3);
    __dt__7DerivedFv (&__1d, 2);
    return 0;
}

```

11

C Source Code (cont'd)

- e.g.,

```
struct __mptr __vtbl__7Derived__c___src_C[] = {
    0, 0, 0,
    0, 0, (__vptp) F1__7DerivedFv,
    0, 0, (__vptp) F2__7DerivedFv,
    0, 0, 0
};

char __pure_virtual_called ();

struct __mptr __vtbl__4Base__c___src_C[] = {
    0, 0, 0,
    0, 0, (__vptp) __pure_virtual_called,
    0, 0, (__vptp) F2__4BaseFv,
    0, 0, 0
};

struct __mptr *__ptbl_vec__c___src_C[] = {
    __vtbl__4Base__c___src_C,
    __vtbl__7Derived__c___src_C,
}
```